Product Datasheet
LED Street Luminaire (150w)



Areas of applications

- Local Roads.
- Express Roads.
- Town Roads.
- Residential Area Roads.
- Pedestrian crossings.
- Parking areas.

Product Features

- Luminaire efficacy up to 140 lm/w.
- Life time 50 K hours (L80).
- Class I Protection.
- Ingress Protection: IP66.
- Failure rate less than 10%.
- High Pressure Die Cast Aluminum.


APPROVED
الهيئة العامة للطرق و الكباري و النقل البري
General Authority For Roads, Bridges And Land Transport
(GARBLT)


5 YEAR WARRANTY
IP66
PHILIPS Xitanium LED driver
LUMILEDS
LM80

Manufacturer	Storm Electric (Storm LED)	
Input Power	150 W	
Input Voltage Range	202 –254 Vac	
Power Factor	≥ 0.95	
Input Current	≤ 0.74 A	
Total Harmonic Distortion (THD)	≤ 10%	
Frequency Range	50 - 60 Hz	
Driver	Philips LED Driver	
Driver Efficiency	92%	
Luminaire Efficacy	130 - 140 lm/w	
LED Type	Lumileds	
Output Lumen	19500 - 21000 lm	
Color Rendering Index (CRI)	Ra ≥ 80	
Color Temperature (CCT)	3000 K - 6500 K	
SDCM	1-3 Steps	
Beam Angle	120°	
Ambient Temperature & Humidity	-40°C to 55°C 10% to 90%	
Protection	Over Power Protection Surge Protection 4 kV	
Ingress Protection	IP66	
Fixture Weight	4.8 Kg	
Order Code	(3000k) (4000k) (5000k) (6500k)	SLP-150W-30L-PB15 SLP-150W-40L-PB15 SLP-150W-50L-PB15 SLP-150W-65L-PB15

Notes: Luminaire power may be (±10%) of rated power & lumen may be (-10%) of rated lumen according to Standard (IEC 62717)

Dimensions


30
14
19.5
8
19
2.85
63
22


UV resistant Polycarbonate
LUMILEDS
LUXEON 3030 2D
(square LES)
PHILIPS
High Efficient Heat Sink